



NATURE & WILDLIFE

THE GREAT WALL OF CHINA

THE GREAT WALL OF CHINA

THE GREAT WALL OF CHINA


THE GREAT WALL OF CHINA




ST series



- Aluminum Die casting cabinet
- 3840Hz Refresh
- Full Front Maintenance
- Optional:P1.25,P1.53,P1.66,P1.86,P2.5
- Fanless,No Noise
- W640xH480,W640xH640,W960xH480mm




Catalogue



Features

ST series



Seamless Splice

No bezel, Vivid visual



High Refresh: 3840Hz



No Scanning line, No jitter



MPLED RB series



Other company

High Contrast




5000:1 contrast ratio, Vivid video & Picture



MPLED ST series

Other company

Multiple installation methods



Wall mounted Directly



Stacking



Hanging



Corner




Cube Column




Full Front Maintenance

Save much space and make the screen slim



Multi size splicing

- W640xH480mm,W640xH640mm,W960xH480mm
- Optional:P1.25,P1.56,P1.66,P1.86,P2.5
- Same pixel pitch screen can use different cabinet size to combine



All-in-One LED Display

2560x1440mm and 3200*1920mm



Application



Indoor

Indoor Project reference



Europe 14.75m² P1.86 Indoor LED Display



South Korea 150m² P2.5 Indoor LED Display

Indoor


More project reference

- Church
- School
- Studio
- Fashion Show
- Wedding
- Product Lanuch
- Press conference
- Concert
- Festival
- Resturant
- Stage



Specification

Specification & Package



Indoor

High refresh and Vivid color

Indoor Specification	P1.25	P1.53	P1.86	P2.5
LED Configuration	SMD1010	SMD1212	SMD1515	SMD2121
Pixel Density(dots/m ²)	640000dots/m ²	422500dots/m ²	288888dots/m ²	160000dots/m ²
Module size(mm)	320x160mm			
Cabinet size(mm)	640x480mm			
Cabinet resolution(mm)	512x384dots	416x312dots	344x258dots	256x192dots
Cabinet weight(kg)	8kg			
IP Rating	IP40			
Brightness(nits)	600-800nits adjustable			
Viewing Angle(H/V)	Horizontal:160degree,Vertical:140degree			
Gray Scale(bit)	16bit			
Max Power Consumption	600W			
Ave Power Consumption	180W			
Refresh	3840Hz			
Input Voltage(V)	110V-240V 50/60Hz			
Operate Temperature/Humidity	Temperature -20°C-60°C , 10%-90% Humidity			
Lifespan	100000H			

Package


Plywooden package



8 in 1 (640x480mm panel size)
Package size :L775xW725xH665 mm

Company Profile

About the company





15000m² Workshop
3000m² Capacity
300+ Employee




23 STM Machine
16 Automatic Shrink Machine
14 Automatic Solder Paste
4 Reflow Soldering
2 Glue Filling Machine
Brushing Machine



Certificate

Corporate qualifications



CE, ROHS, FCC, UL, CB, PSE, IP65/IP54; ISO9001, ISO14001 etc



- Go beyond cooperating customers to contact their customer
- Deceive or cheat customers
- Harm others to benefit oneself
- Ship unqualified products

Above 4 point is our company baseline,we never do it

To be a realiable and trusted company,first to be a reliable and trusted person